

Product Selection Guide



Model Name	UC-7420	UC-7410	UC-7408	UC-7402
CPU	Intel XScale IXP-422 266 MHz	Intel XScale IXP-422 266 MHz	Intel XScale IXP-422 266 MHz	Intel XScale IXP-422 266 MHz
RAM	128 MB	128 MB	128 MB	128 MB
Flash	32 MB	32 MB	32 MB	32 MB
OS	Linux, WinCE	Linux, WinCE	Linux, WinCE	Linux
LAN	Auto-sensing 10/100 Mbps x 2 with built-in 1.5 KV magnetic isolation protection, RJ45 Connector			
Serial Port	RS-232/422/485 x 8 RJ45 Connector	RS-232/422/485 x 8 RJ45 Connector	RS-232/422/485 x 8 RJ45 Connector	N/A
Serial Protection	15 KV ESD for all signals			N/A
Data Bits	5, 6, 7, 8			N/A
Stop Bits	1, 1.5, 2			N/A
Parity	none, even, odd, space, mark			N/A
Flow Control	RTS/CTS, XON/XOFF, RS-485 ADDC™			N/A
Speed	50 bps to 921.6 Kbps			N/A
Serial Console	RS-232 x 1 RJ45 Connector	RS-232 x 1 RJ45 Connector	RS-232 x 1 RJ45 Connector	RS-232 x 1 RJ45 Connector
DI/DO	N/A	N/A	DI x 8, DO x 8	N/A
USB 2.0 Hosts	2	N/A	N/A	N/A
USB 1.1 Client	1*	1*	1*	1*
PCMCIA	Cardbus x 1**	N/A	Cardbus x 1**	Cardbus x 1**
Storage Expansion	CompactFlash x 1***	N/A	CompactFlash x 1***	CompactFlash x 1***
LCM	128 x 64 dots	128 x 64 dots	N/A	N/A
Keypad	5	5	N/A	N/A
Real Time Clock	Yes	Yes	Yes	Yes
Buzzer	Yes	Yes	Yes	Yes
Reset Button	H/W Reset x 1 Reset to Default x 1	H/W Reset x 1 Reset to Default x 1	H/W Reset x 1 Reset to Default x 1	H/W Reset x 1 Reset to Default x 1
Power Input	12 to 48 VDC	12 to 48 VDC	12 to 48 VDC	12 to 48 VDC
Power Consumption	12W	10W	8W	7W
Dimensions (W x D x H)	197 x 125 x 44 mm	197 x 125 x 44 mm	197 x 125 x 44 mm	197 x 125 x 44 mm
Weight	875 g	810 g	870 g	830 g
Operating Temperature	-10 to 60°C, (14 to 140°F), 5 to 95% RH			
Storage Temperature	-20 to 80°C, (-4 to 176°F), 5 to 95% RH			
Regulatory Approvals	EMC: CE Class A, FCC Class A Safety: UL, cUL, TUV			
Warranty	5 years	5 years	5 years	5 years