



Firmware for IKS-G6824A Series Release Notes

Version: v5.6	Build: Build_18110820
Release Date: Jan 18, 2019	

Applicable Products

IKS-G6824A Series

Supported Operating Systems

N/A

New Features

Layer 3:

- Support tracking function.

Security Related Functions

- System Notification: Definable successful/failed login notification.
- Password Policy: Password strength can be set.
- Account Lockout Policy: Failure threshold and lockout time can be set.
- Log Management: Full log handling.
- Remote Access Interface Enable/Disable.
- Configuration Encryption with password.
- Support SSL certification import.
- Support MAC authentication bypass via RADIUS authentication.
- MAC Address access control list or MAC address filtering.
- Protect against MAC flooding attack by MAC address sticky.
- NTP authentication to prevent NTP DDoS attack.
- Login Authentication: Support primary & backup database servers (RADIUS / TACACS+ / Local Account).
- Login Authentication via RADIUS Server: Support Challenge Handshake Authentication Protocol (CHAP) authentication mechanism.
- RADIUS Authentication: Support EAP-MSCHAPv2 (For Windows 7).
- MXview Security View Feature Support* (with MXstudio V2.4).

Redundancy

- Turbo Ring v2, Turbo Chain Support Port Trunking

Enhancements

- Web GUI supports web browser Chrome 65.0
- CLI: Supports Multiple Sessions (up to six).
- SMTP Supports Transport Layer Security (TLS) Protocol and Removes SSL v2/v3.
- SNMPv3 Traps and Informs.
- Display Issues with Java Applet.
- Fiber Check: Add Threshold Alarm.
- Static Port Lock with VLAN filtering option.
- When GbE Port Speed is [Auto], MDI/MDIX is [Auto] Fixed.
- Web UI/CLI Command Enhancement and Modification.

Bugs Fixed

- Fix abnormal display of packet counter in the web GUI.
- When the device receives large amounts of BPDU packets on a port, the RSTP function does not enable, which might cause the device to reboot.



- If there is an '&' in either the Switch Name or Switch Location column, the description will not display properly on the relevant page.

Changes

- Rate limit adds more options on the ingress rate

Notes

Suggestion:

- Reconfigure the device once you have upgraded to v5.x
- To ensure that the system remains stable, do not export configurations from v4.x or prior into v5.x or later



Version: v4.5	Build: Build_16112110
Release Date: Dec 28, 2016	

Applicable Products

IKS-G6824A-20GSFP-4GTXSFP-HV-HV, IKS-G6824A-4GTXSFP-HV-HV, IKS-G6824A-8GSFP-4GTXSFP-HV-HV, IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6824A-4GTXSFP-HV-HV-T, IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- Added DSCP remark function.
- Added Traceroute function.

Enhancements

- Encrypted all security passwords and keys in web user interface and the CLI.

Bugs Fixed

- VRRP did not work on RSTP ports.
- VRRP state unexpectedly changed when it took too much time to change the IGMP querier.
- VRRP state unexpectedly changed when both VRRP Fast Switchover mode is enabled and Port Trunking is set.
- Configurations could not be imported through command line, when VRRP Fast Switchover mode is set with more than 16 entries.
- Device occasionally rebooted when enabling OSPF.

Changes

N/A

Notes

N/A



Version: v4.2	Build: Build_15062312
Release Date: N/A	

Applicable Products

IKS-G6824A-20GSFP-4GTXSFP-HV-HV, IKS-G6824A-4GTXSFP-HV-HV, IKS-G6824A-8GSFP-4GTXSFP-HV-HV, IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6824A-4GTXSFP-HV-HV-T, IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- Added new Multicast Fast Forwarding mode.
- Added new VRRP Fast Switchover mode.
- Added new Multicast Local Route.

Enhancements

- Increased IGMP Groups to 4096 (original 1000 groups).
- Improved Turbo Chain link status check mechanism at the head port.

Bugs Fixed

- Device rebooted when using CLI commands to back up device configurations to TFTP server.
- Device rebooted when using CLI commands to change SNMP v3 data encryption key and the length of key is over than 100 characters.

Changes

N/A

Notes

N/A



Version: v4.1	Build: Build_15030209
Release Date: N/A	

Applicable Products

IKS-G6824A-20GSFP-4GTXSFP-HV-HV, IKS-G6824A-4GTXSFP-HV-HV, IKS-G6824A-8GSFP-4GTXSFP-HV-HV, IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6824A-4GTXSFP-HV-HV-T, IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

N/A

Enhancements

N/A

Bugs Fixed

- PIM-SM multicast forwarding issues.
- Randomly hang issue when booting up.
- Topology drawing issue on MXview.
- In IGMPv3, failed to forward multicast packets on MSTP DISABLED-STATUS port.
- Failed to add Static default route (0.0.0.0/0) through the web console.
- Randomly failed to recognize Moxa SFP modules.
- In OSPF routing protocol, 10 G ports had incorrect path cost.
- Randomly failed to connect to ABC-02.
- HTTPS certification validity issue.
- There was a rebooting issue when TFTP upgraded firmware with incorrect CLI command.
- ACL CLI command failed on rules when Ether-type is 0 or IP-protocol is 0.
- Hang issue when IGMP join and leave frequently.

Changes

N/A

Notes

N/A



Version: v4.0	Build: Build_14093015
Release Date: N/A	

Applicable Products

IKS-G6824A-20GSFP-4GTXSFP-HV-HV, IKS-G6824A-4GTXSFP-HV-HV, IKS-G6824A-8GSFP-4GTXSFP-HV-HV, IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6824A-4GTXSFP-HV-HV-T, IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- First release for IKS-G6824A Series.

Enhancements

N/A

Bugs Fixed

N/A

Changes

N/A

Notes

N/A