

# PWR 電源模組系列

適用於 Moxa 交換器的可熱插拔電源模組



## 特色與優點

- -40°C 至 85°C 寬範圍操作溫度
- 符合 IEC 61850-3 及 IEEE 1613 規範

## 認證



## 簡介

PWR 電源模組系列可熱插拔電源模組 專為 Moxa 交換器設計。電源模組可讓受支援的 交換器使用 24/48 VDC 或 110/220 VAC/VDC。

## 規格

### Power Parameters

Input Voltage	<p>PWR-HV-P48: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-LV-P48: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-HV-NP: 110/220 VDC/VAC for the switch system</p> <p>PWR-LV-NP: 24/48 VDC for the switch system</p>
Operating Voltage	<p>PWR-HV-P48: 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-LV-P48: 18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-HV-NP: 88 to 300 VDC, 90 to 264 VAC for the switch system</p> <p>PWR-LV-NP: 18 to 72 VDC for the switch system</p>
Reverse Polarity Protection	Supported
Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC or 0.5 A @ 125 VAC

## Physical Characteristics

Weight	PWR-HV-P48: 360 g (0.79 lb) PWR-LV-P48: 360 g (0.79 lb) PWR-HV-NP: 340 g (0.75 lb) PWR-LV-NP: 340 g (0.75 lb)
--------	--

## MTBF

Time	PWR-HV-P48: 1,530,831 hrs PWR-LV-P48: 1,388,747 hrs PWR-HV-NP: 2,556,214 hrs PWR-LV-NP: 2,710,293 hrs
Standards	Telcordia (Bellcore), GB

## Warranty

Warranty Period	5 years
Details	See <a href="http://www.moxa.com/tw/warranty">www.moxa.com/tw/warranty</a>

## 訂購資訊

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-HV-P48	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series
PWR-HV-NP	110/220 VDC/VAC	88-300 VDC, 90-264 VAC	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-P48	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series
PWR-LV-NP	24/48 VDC	18-72 VDC	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series

© Moxa Inc. 版權所有. 2023 年 11 月 17 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。