

IKS-6726Aシリーズ

24+2Gポートモジュール型マネージドイーサネットスイッチ



機能とメリット

- 銅線およびファイバー用のギガビットポート2個と高速イーサネットポート24個
- Turbo RingとTurbo Chain（リカバリ時間はスイッチ250台で20 ms未満）¹、およびSTP/RSTP/MSTPによりネットワークの冗長性を実現
- モジュール式の設計のため様々なメディアの組み合わせから選択することが可能
- 動作温度範囲-40～75°C
- 簡単に視覚化された産業用ネットワーク管理を行うためのMXstudioに対応
- V-ON™により、ミリ秒レベルのマルチキャストデータとビデオネットワークの回復を確実に実現

認証



製品紹介

IKS-6726Aシリーズは、交通管制システムや海洋アプリケーションなど、産業およびビジネスにおけるミッションクリティカルなアプリケーションの厳しい要求を満たすように設計されています。IKS-6726Aのギガビットおよび高速イーサネットバックボーン、冗長リング、24/48 VDCまたは110/220 VACデュアル絶縁冗長電源により、通信の信頼性が向上するとともに、ケーブルや配線にかかるコストを削減できます。

また、IKS-6726Aのモジュール型設計により、ネットワーク計画が容易になり、最大2つのギガビットポートと24個の高速イーサネットポートを設置できるため、柔軟性が向上します。

その他の機能とメリット

- 主なマネージド機能をすばやく設定するためのコマンドラインインターフェース（CLI）
- 各ポリシーに応じてIPアドレスを割り当てるDHCP Option 82
- デバイスの管理および監視用のEtherNet/IP、PROFINET、およびModbus TCPプロトコルをサポート
- マルチキャストトラフィックをフィルタリングするIGMPスヌーピングおよびGMRP
- ポートベースのVLAN、IEEE 802.1Q VLAN、GVRPでネットワークプランニングを簡素化
- QoS（IEEE 802.1p/1Q and TOS/DiffServ）
- 最適な帯域幅利用のIEEE 802.3ad、LACP
- ラインスワップ高速リカバリ
- TACACS+、IEEE 802.1X、SNMPv3、HTTPS、およびSSHにより、ネットワークセキュリティを強化
- 異なるレベルのネットワーク管理を実現するSNMPv1/v2c/v3
- プロアクティブで効率の高いネットワーク監視のためのRMON
- 帯域幅管理により、許可されたMACアドレスへのアクセスを制限する「ポートのロック」で、予期しないネットワークアクセスを防止
- オンラインデバッグ用のポートミラーリング
- メールとリレー出力を通じた例外検出による自動警告
- 接続されたデバイスのIPアドレスの自動復旧
- Webブラウザ、Telnet/シリアルコンソール、CLI、Windowsユーティリティ、ABC-02-USB自動バックアップコンフィギュレータによる設定が可能

仕様

Input/Output Interface

Alarm Contact Channels	1 relay output with current carrying capacity of 1 A @ 24 VDC
------------------------	---

Ethernet Interface

10/100BaseT(X) Ports (RJ45 connector)	8
Combo Ports (10/100/1000BaseT(X) or 100/1000BaseSFP)	2

1. ポートリンク速度が1ギガビット以上の場合、リカバリ時間は50 ms未満となります。

Module	2 modular slots for any 8-port or 6-port Interface Modules with 10/100BaseT(X), 100BaseFX (SC/ST connector), or 100Base SFP ²
Standards	IEEE 802.1D-2004 for Spanning Tree Protocol IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1s for Multiple Spanning Tree Protocol IEEE 802.1w for Rapid Spanning Tree Protocol IEEE 802.1X for authentication IEEE 802.3 for 10BaseT IEEE 802.3ab for 1000BaseT(X) IEEE 802.3ad for Port Trunk with LACP IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3x for flow control IEEE 802.3z for 1000BaseSX/LX/LHX/ZX

Ethernet Software Features

Management	Back Pressure Flow Control BOOTP DDM DHCP Option 66/67/82 DHCP Server/Client Flow control IPv4/IPv6 LLDP Port Mirror RARP RMON SCP SMTP SNMP Inform SNMPv1/v2c/v3 Syslog Telnet TFTP
Filter	802.1Q BPDU Filter BPDU Guard GMRP GVRP IGMP v1/v2/v3
Redundancy Protocols	Link Aggregation MRP MSTP RSTP STP Turbo Chain Turbo Ring v1/v2 V-ON
Security	Access control list Broadcast storm protection HTTPS/SSL MAB authentication NTP authentication Port Lock RADIUS SSH TACACS+
Time Management	SNTP

2. 高速イーサネットモジュール製品情報については、IM-6700Aデータシートを参照してください。

Industrial Protocols	EtherNet/IP Modbus TCP PROFINET
MIB	Ethernet-like MIB MIB-II P-BRIDGE MIB Q-BRIDGE MIB RMON MIB Groups 1, 2, 3, 9 RSTP MIB

Switch Properties

IGMP Groups	2048
Jumbo Frame Size	9.6 KB
MAC Table Size	16 K
Max. No. of VLANs	64
Packet Buffer Size	12 Mbits
Priority Queues	4
VLAN ID Range	VID 1 to 4094

USB Interface

Storage Port	USB Type A
--------------	------------

Serial Interface

Console Port	USB-serial console (Type B connector)
--------------	---------------------------------------

Power Parameters

Input Voltage	IKS-6726A-2GTXSFP-24-T: 24 VDC IKS-6726A-2GTXSFP-24-24-T: 24 VDC (redundant dual inputs) IKS-6726A-2GTXSFP-48-T: 48 VDC IKS-6726A-2GTXSFP-48-48-T: 48 VDC (redundant dual inputs) IKS-6726A-2GTXSFP-HV-T: 110/220 VAC IKS-6726A-2GTXSFP-HV-HV-T: 110/220 VAC (redundant dual inputs)
Operating Voltage	IKS-6726A-2GTXSFP-24-T: 18 to 36 VDC IKS-6726A-2GTXSFP-24-24-T: 18 to 36 VDC IKS-6726A-2GTXSFP-48-T: 36 to 72 VDC IKS-6726A-2GTXSFP-48-48-T: 36 to 72 VDC IKS-6726A-2GTXSFP-HV-T: 85 to 264 VAC IKS-6726A-2GTXSFP-HV-HV-T: 85 to 264 VAC
Input Current	1.1/0.6 A @ 24/48 VDC 0.46/0.31 A @ 110/220 VAC Note: These are the input current ratings for the device with the maximum number of modules installed.
Power Consumption (Max.)	26.4/28.8 W @ 24/48 VDC 29.28/31.92 W @ 110/220 VAC Note: These are the power consumption ratings for the device with the maximum number of modules installed.
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

IP Rating	IP30
Dimensions	440 x 44 x 280 mm (17.32 x 1.37 x 11.02 in)

Weight	4100 g (9.05 lb)
Installation	Rack mounting

Environmental Limits

Operating Temperature	-40 to 75°C (-40 to 167°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

Safety	EN 60950-1 UL 60950-1
EMC	EN 55032/24
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF
Railway	EN 50121-4
Maritime	ABS DNV LR NK
Freefall	IEC 60068-2-32
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6

MTBF

Time	IKS-6726A-2GTXSFP-24-T: 851,519 hrs IKS-6726A-2GTXSFP-24-24-T: 851,519 hrs IKS-6726A-2GTXSFP-48-T: 852,899 hrs IKS-6726A-2GTXSFP-48-48-T: 852,899 hrs IKS-6726A-2GTXSFP-HV-T: 942,524 hrs IKS-6726A-2GTXSFP-HV-HV-T: 932,847 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty


Package Contents

Device	1 x IKS-6726A Series switch
Cable	1 x USB type A male to USB type B male
Installation Kit	2 x rack-mounting ear 6 x cap, plastic, for SFP slot
Power Supply	IKS-6726A-2GTXSFP-HV-T: 1 x power cord, EU type IKS-6726A-2GTXSFP-HV-HV-T: 2 x power cord, EU type IKS-6726A-2GTXSFP-HV-T: 1 x power cord, US type

	IKS-6726A-2GTXSFP-HV-HV-T: 2 x power cord, US type
Documentation	1 x quick installation guide 1 x warranty card
Note	SFP modules and/or modules from the IM-6700A Module Series need to be purchased separately for use with this product.

寸法

単位：mm（インチ）



注文情報

Model Name	Combo Ports10(10/100/1000BaseT(X) or 100/1000BaseSFP)	100BaseSFP Slots	10/100BaseT(X) Ports10RJ45 Connector	100BaseFX Ports	Operating Temp.	Input Voltage	Redundant Dual Input
IKS-6726A-2GTXSFP-HV-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	110/220 VAC power supply	-
IKS-6726A-2GTXSFP-HV-HV-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	110/220 VAC power supply	P
IKS-6726A-2GTXSFP-24-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	24 VDC power supply	-
IKS-6726A-2GTXSFP-24-24-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	24 VDC power supply	P
IKS-6726A-2GTXSFP-48-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	48 VDC power supply	-
IKS-6726A-2GTXSFP-48-48-T	2	Up to 18	Up to 24	Up to 12	-40 to 75°C	48 VDC power supply	P

アクセサリ（別売）

IM-6700A Module Series

IM-6700A-2MSC4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports
IM-6700A-2MST4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports
IM-6700A-2SSC4TX	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports
IM-6700A-4MSC2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connector, 2 10/100BaseT(X) ports

IM-6700A-4MST2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports
IM-6700A-4SSC2TX	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports
IM-6700A-6MSC	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors
IM-6700A-6MST	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors
IM-6700A-6SSC	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors
IM-6700A-8PoE	Fast Ethernet PoE+ module with 8 100BaseT(X) PoE/PoE+ ports (for IKS-6728A-8PoE Series only)
IM-6700A-8SFP	Fast Ethernet module with 8 100BaseSFP slots
IM-6700A-8TX	Fast Ethernet module with 8 10/100T(X) ports

Storage Kits

ABC-02-USB	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature
------------	---

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXLC	SFP module with 1 1000BaseEZX port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZX port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature

SFP-1GLHXLC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXLC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXLC	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature
SFP-1GLSXLC-T	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXLC	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature
SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature

Power Cords

PWC-C13CN-3B-183	Power cord with three-prong CN plug, 1.83 m
PWC-C7EU-2B-183	Power cord with EU plug, 2.5A/250V, 1.83 m
PWC-C13US-3B-183	Power cord with US plug, 1.83 m
PWC-C7US-2B-183	Power cord with US plug, 10A/125V, 1.83 m
PWC-C7AU-2B-183	Power cord with AU plug, 2.5A/250V, 1.83 m
PWC-C13EU-3B-183	Power cord with EU/KR plug, 1.83 m
PWC-C13UK-3B-183	Power cord with UK plug, 1.83 m
PWC-C7UK-2B-183	Power cord with UK plug, 2.5A/250V, 1.83 m
PWC-C13AU-3B-183	Power cord with AU plug, 1.83 m

Software

MXview-50	MXview license for 50 nodes
MXview-100	MXview license for 100 nodes
MXview-250	MXview license for 250 nodes
MXview-500	MXview license for 500 nodes
MXview-1000	MXview license for 1000 nodes
MXview-2000	MXview license for 2000 nodes
MXview Upgrade-50	MXview license expansion for 50 nodes

© Moxa Inc. All rights reserved. 2026年2月11日更新。

Moxa Inc.の明白な許可を書面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。