

PWR-A 電源模組系列

MDS-G4000-4XGS 系列的熱插拔電源模組

特色與優點

- -40°C 至 85°C 寬範圍操作溫度
- 符合 IEC 61850-3 及 IEEE 1613 規範



認證



簡介

PWR-A 電源模組系列熱插拔電源模組專為 Moxa 交換器而設計。電源模組允許支援的交換器使用 28/48 VDC、110/220 VAC/VDC 或使用 48 VDC 於 PoE 系統。

規格

Power Parameters

Input Voltage	PWR-HV-P48-A: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices) PWR-LV-P48-A: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)
Operating Voltage	PWR-HV-P48-A: 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems PWR-LV-P48-A: 18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems
Reverse Polarity Protection	Supported
Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC or 0.5 A @ 125 VAC
Physical Characteristics	
Weight	PWR-HV-P48-A: 420 g (0.93 lb) PWR-LV-P48-A: 400 g (0.88 lb)
MTBF	
Time	PWR-HV-P48-A: 1,530,831 hrs PWR-LV-P48-A: 1,388,747 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/tw/warranty

訂購資訊

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-HV-P48-A	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-P48-A	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series

© Moxa Inc. 版權所有.2023 年 11 月 29 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。