

RKP-C110 系列

配備第 11 代 Intel® Core™ Tiger Lake 處理器基礎型號及高介面型號的機架安裝電腦



特色與優點

- 無風扇設計 1U 機架安裝電腦
- 第 11 代 Intel® Celeron® 或 Intel® Core™ i3、i5 或 i7 處理器
- 最多 12 個 LAN 埠與最多 10 個串列埠的豐富介面選項
- 12/24 VDC 與雙 100 至 240 VAC/VDC 電源輸入選項
- 統一前面板連接設計，可輕鬆存取介面
- -30 至 60°C 操作溫度範圍

認證



簡介


RKP-C110 機架式電腦採用第 11 代 Intel® Celeron® 或 Intel® Core™ i3, i5 或 i7，並具備多樣化的介面配置，包括最多 12 個 Gigabit 乙太網路連接埠、10 個軟體可選擇的 RS-232/422/485 串列埠及 8 個數位輸入與 8 個數位輸出。通訊介面全都位於前面板，方便在工業應用中進行存取與擴充。兩個手動旋轉式 2.5" SSD 儲存裝置與可外部更換的 RTC 電池設計為更易用的選項提供可靠、耐用及多樣化的平台。

設計為 1U 標準外型無風扇機架安裝電腦，操作溫度範圍在 -30 至 60°C，並內建 TPM 2.0 模組，RKP-C110 電腦是可靠安全的理想運算平台，適用於極端操作環境下的工業應用。


外觀

前視圖


RKP-C110-C1-T/C3-T/C5-T/C7-T/C1-T-Win10/C3-T-Win10/C5-T-Win10/C7-T-Win10 型號




RKP-C110-C1-8L-T/C3-8L-T/C5-8L-T/C7-8L-T 型號




RKP-C110-C1-8C-T/C3-8C-T/C5-8C-T/C7-8C-T 型號



RKP-C110-C1-2L4C-T/C3-2L4C-T/C5-2L4C-T/C7-2L4C-T 型號




RKP-C110-C1-2HV-T/C3-2HV-T/C5-2HV-T/C7-2HV-T 型號




後視圖

RKP-C110-C1-2HV-T/C3-2HV-T/C5-2HV-T/C7-2HV-T 型號



其他 所有型號



規格

Computer

CPU	RKP-C110-C1 models: Intel® Celeron® 6305E "(Dual core, 4M cache, 1.80 GHz) RKP-C110-C3 models: Intel® Core™ i3-1115G4E (Quad core, 4M cache, 3 GHz, Base: 2.20 GHz) RKP-C110-C5 models: Intel® Core™ i5-1145G7E (Quad core, 8M cache, 2.60 GHz, Base: 1.50 GHz) RKP-C110-C7 models: Intel® Core™ i7-1185G7E (Quad core, 12M cache, 2.80 GHz, Base: 1.80 GHz)
System Memory Slot	SODIMM DDR4 slots x 1, up to 32 GB max.
System Memory Pre-installed	8 GB DDR4
Storage Slot	2.5-inch SSD slots x 2 (SATAIII interface) RAID 0/1 support
Supported OS	Windows images and drivers supported: - Windows 11 IoT Ent LTSC 2024 64-bit - Windows 10 IoT Ent LTSC 2021 64-bit - Windows 11 Professional 64-bit - Windows Server 2022 (driver support only) Linux image supported: - Debian 12 (kernel 6.10) Linux drivers supported: - Debian 12 (kernel 6.10) - Ubuntu 22.04 LTS/HWE - RHEL 9 (kernel 5.14)
Graphics Controller	Intel® Iris® Xe Graphics

Computer Interface

Ethernet Ports	RKP-C110-C1-8L-T/C3-8L-T/C5-8L-T/C7-8L-T models: Auto-sensing 10/100/1000 Mbps ports (RJ45 connector) x 12 RKP-C110-C1-2L4C-T/C3-2L4C-T/C5-2L4C-T/C7-2L4C-T models: Auto-sensing 10/100/1000 Mbps ports (RJ45 connector) x 6 All other models: Auto-sensing 10/100/1000 Mbps ports (RJ45 connector) x 4
Serial Ports	RKP-C110-C1-8C-T/C3-8C-T/C5-8C-T/C7-8C-T models: RS-232/422/485 ports x 10, software selectable (DB9 male) RKP-C110-C1-2L4C-T/C3-2L4C-T/C5-2L4C-T/C7-2L4C-T models: RS-232/422/485 ports x 6, software selectable (DB9 male) All other models: RS-232/422/485 ports x 2, software selectable (DB9 male)
USB 3.0	USB 3.0 hosts x 3, type-A connectors
Digital Input	DIs x 8
Digital Output	DOs x 8
TPM	TPM v2.0
Video Output	HDMI 2.0b x 1, (type A connector) VGA x 1, 15-pin D-sub connector (female)
Buttons	Reset button Power button

Ethernet Interface

Magnetic Isolation Protection	1.5 kV (built-in)
-------------------------------	-------------------

Serial Interface

Baudrate	50 bps to 115.2 kbps
Connector	DB9 male
Data Bits	5, 6, 7, 8
Parity	None, Even, Odd, Space, Mark
Stop Bits	1, 1.5, 2
Flow Control	RTS/CTS, XON/XOFF

Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND

Digital Inputs

Connector	Spring-type Euroblock terminal
Sensor Type	Dry contact
Dry Contact	Logic 0: Short to GND Logic 1: Open

Digital Outputs

Connector	Spring-type Euroblock terminal
I/O Type	Sink
Current Rating	200 mA per channel
Voltage	0 to 24 VDC

LED Indicators

System	Power x 1 Storage x 1
LAN	2 per port (10/100/1000 Mbps)

Power Parameters

Input Voltage	12/24 VDC 2HV-T models: 100 to 240 VAC/VDC
Power Connector	Screw-fastened Euroblock terminal
Power Consumption	90 W

Physical Characteristics

Housing	Metal
IP Rating	IP20
Dimensions	440 x 230 x 43.6 mm (17.32 x 9.06 x 1.72 in) 2HV-T models: 440 x 360 x 43.65 mm (17.32 x 14.17 x 1.72 in)
Weight	RKP-C110-C1-8C-T/C3-8C-T/C5-8C-T/C7-8C-T models: 3,610 g (7.95 lb) RKP-C110-C1-2L4C-T/C3-2L4C-T/C5-2L4C-T/C7-2L4C-T models: 3,540 g (7.80 lb) RKP-C110-C1-8L-T/C3-8L-T/C5-8L-T/C7-8L-T models: 3,800 g (8.37 lb) RKP-C110-C1-T/C3-T/C5-T/C7-T/C1-T-Win10/C3-T-Win10/C5-T-Win10/C7-T-Win10 models: 3,350 g (7.38 lb) RKP-C110-C1-2HV-T/C3-2HV-T/C5-2HV-T/C7-2HV-T models: 5,616 g (12.38 lb)
Installation	Rack mounting (standard 1U)

Environmental Limits

Operating Temperature	-30 to 60°C (-22 to 140°F)
Storage Temperature	-40 to 75°C (-40 to 167°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

EMC	EN 55032/35
EMI	CISPR 32, FCC Part 15B Class A BSMI
EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV, Signal: 1 kV IEC 61000-4-6 CS: 3 V IEC 61000-4-8 PFMF: 1 A/m at 50 to 60 Hz

Safety	IEC 62368-1 UL 62368-1 BSMI
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-64
Package Drop Test	ISTA 1A
Package Vibration Test	ISTA 1A

Declaration

Green Product	RoHS, CRoHS, WEEE
---------------	-------------------

Reliability

Time Source	Built-in RTC (real-time clock) with lithium-battery backup
Automatic Reboot Trigger	Built-in WDT

MTBF

Time	493,336 2HV-T models: 1,435,365 hrs hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	3 years
Details	See www.moxa.com/tw/warranty


Package Contents

Device	1 x RKP-C110 Series computer
Installation Kit	2 x terminal block, 10-pin for DI/DOs 1 x terminal block, 2-pin for DC power (non-2HV models only) 1 x terminal block, 5-pin for AC/DC power (2HV models only) 2 x rack-mounting ears with 16 screws (2HV models only)
Documentation	1 x quick installation guide 1 x warranty card

尺寸


RKP-C110-C1-T/C3-T/C5-T/C7-T/C1-T-Win10/C3-T-Win10/C5-T-Win10/C7-T-Win10 型號

單位：公釐（英吋）




RKP-C110-C1-2HV-T/C3-2HV-T/C5-2HV-T/C7-2HV-T 型號

單位：公釐（英吋）




RKP-C110-C1-8L-T/C3-8L-T/C5-8L-T/C7-8L-T 型號

單位：公釐（英吋）




RKP-C110-C1-8C-T/C3-8C-T/C5-8C-T/C7-8C-T 型號

單位：公釐（英吋）



RKP-C110-C1-2L4C-T/C3-2L4C-T/C5-2L4C-T/C7-2L4C-T 型號

單位：公釐（英吋）



訂購資訊

Model Name	CPU	RAM	Storage Slots	OS Preinstalled	LAN/Serial	USB 3.0	DIs/ DOs	Video Outputs	Power Input
RKP-C110-C1-T	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	-	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C1-T-Win10	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	Win 10 LTSC (64 GB SSD)	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C1-8L-T	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	-	12/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C1-8C-T	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	-	4/10	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C1-2L4C-T	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	-	6/6	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C5-T	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	-	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C5-T-Win10	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	Win 10 LTSC (64 GB SSD)	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C5-8L-T	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	-	12/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC

Model Name	CPU	RAM	Storage Slots	OS Preinstalled	LAN/Serial	USB 3.0	DIs/ DOs	Video Outputs	Power Input
RKP-C110-C5-8C-T	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	–	4/10	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C5-2L4C-T	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	–	6/6	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C7-T	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	–	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C7-T-Win10	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	Win 10 LTSC (64 GB SSD)	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C7-8L-T	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	–	12/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C7-8C-T	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	–	4/10	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C7-2L4C-T	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	–	6/6	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	12/24 VDC
RKP-C110-C1-2HV-T	Intel® Celeron® 6305E	8 GB	2 x 2.5" SSD	–	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	100 to 240 VAC/VDC
RKP-C110-C3-2HV-T	Intel® Core™ i3-1115G4E	8 GB	2 x 2.5" SSD	–	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	100 to 240 VAC/VDC
RKP-C110-C5-2HV-T	Intel® Core™ i5-1145G7E	8 GB	2 x 2.5" SSD	–	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	100 to 240 VAC/VDC
RKP-C110-C7-2HV-T	Intel® Core™ i7-1185G7E	8 GB	2 x 2.5" SSD	–	4/2	3	8 x DIs 8 x DOs	1 x VGA 1 x HDMI	100 to 240 VAC/VDC

© Moxa Inc. 版權所有.2025 年 6 月 24 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。