

ioPAC 8600 系列 (86M) 模組

堅固型模組，適用於 ioPAC 8600 系列



特色與優點

- 符合所有 EN 50155 標準強制性測試項目¹
- 符合 EN 50121-4 標準
- 堅固輕巧設計，適用於惡劣環境
- 擴充 ioPAC 8600 系列之 I/O 與通訊能力
- 寬操作溫度範圍-40 至 75°C (-40 至 167°F)
- 通道間隔離的數位輸入及輸出
- 24 至 110V DI/O 模組與通用電源輸入範圍模組
- 支援用於 CAN 2.0 A/B 通訊之控制器區域網路 (CAN bus)

認證



EN 50155



EN 50121-4



簡介

Moxa ioPAC 8600 系列 86M 模組包含通道間隔離的 DI、通道間隔離的 DO、繼電器以及 AO，為 ioPAC 8600 系列裝置提供更多 I/O 選擇。ioPAC 8600 也可使用 85M 模組，讓用戶有多種選項可供選擇，以挑選最適合其目標應用的 I/O 組合。所有 86M 模組都是為軌道產業應用，並且符合 EN 50121-3-2、EN 50121-4 以及所有 EN 50155 標準的強制性測試項目。此外，這些模組均支援 -40 至 75°C 的寬操作溫度範圍，在惡劣環境下也能可靠地運作。

規格

Input/Output Interface

Digital Input Channels	86M-1620D-T: 16 86M-1832D-T: 8
Digital Output Channels	86M-2821D-T: 8 86M-2830D-T: 8
Relay Channels	86M-2604D-T: 6
Analog Output Channels	86M-4420-T: 4
2-Wire Ethernet Ports	86M-5212U-T: 2
CAN Ports	86M-5250-T: 2
Isolation	3k VDC or 2k Vrms

Digital Inputs

Connector	Spring-type Euroblock terminal
Voltage	86M-1620D-T: 24 to 110 VDC 86M-1832D-T: 24 VDC
Channel-to-Channel Isolation	86M-1832D-T: 1k VDC
Counter Frequency	86M-1832D-T: 5k Hz

1. 此產品適合用於符合 EN 50155 標準的軌道車輛應用。按一下此處取得更詳細內容：www.moxa.com/doc/specs/EN_50155_Compliance.pdf

Debouncing Function	86M-1620D-T: Software enable/disable
Debouncing Time	86M-1620D-T: 1 to 15 ms (software-selectable)
Digital Filtering Time Interval	86M-1832D-T: Software configurable
I/O Mode	86M-1620D-T: DI 86M-1832D-T: DI, event counter, or frequency
Points per COM	86M-1620D-T: 8 channels
Scan on Time	86M-1620D-T: 0.5 ms
Scan Period	86M-1620D-T: 8 ms (typical)
Sensor Type	86M-1620D-T: PNP 86M-1832D-T: Wet Contact (NPN or PNP)
Wet Contact (DI to COM)	86M-1832D-T: On: 10 to 30 VDC 86M-1832D-T: Off: 0 to 3 VDC 86M-1620D-T: On: > 0.3 times external power voltage 86M-1620D-T: Off: < 0.15 times external power voltage

Digital Outputs

Connector	Spring-type Euroblock terminal
Voltage	86M-2830D-T: 24 VDC 86M-2821D-T: 24 to 110 VDC
Current Rating	86M-2821D-T: 1500 mA per channel 86M-2830D-T: 200 mA per channel
I/O Mode	DO or PWM
I/O Type	86M-2821D-T: Source 86M-2830D-T: Sink
Over-Voltage Protection	86M-2821D-T: 160 VDC 86M-2830D-T: 41 VDC
Short-Circuit Protection	86M-2821D-T: 2800 mA @ 25°C 86M-2830D-T: 750 mA @ 25°C
Pulse Output Frequency	86M-2821D-T: 100 Hz 86M-2830D-T: 1 kHz

Relays

Connector	Spring-type Euroblock terminal
I/O Mode	Relay or PWM
Contact Current Rating	Resistive load: 5 A @ 30 VDC, 250 VAC
Contact Resistance	100 milli-ohms (max.)
Electrical Endurance	60,000 operations @ 5 A resistive load
Initial Insulation Resistance	1,000 mega-ohms (min.) @ 500 VDC
Mechanical Endurance	5,000,000 operations
Pulse Output Frequency	0.33 Hz at rated load
Type	Form A (N.O.) power relay

Analog Outputs

Connector	Spring-type Euroblock terminal
I/O Mode	Static or waveform mode
Accuracy	±0.1% FSR @ 25°C ±0.3% FSR @ -40 to 75°C
Current Load Resistance	External 24 VDC power: 1000 ohms Internal power: 400 ohms
Output Range	0 to 10 VDC 0 to 20 mA -10 to 10 V 4 to 20 mA
Resolution	12-bit
Voltage Output	10 mA (max.)
Waveform Frequency	125 Hz
Waveform Type	Sine, Square, Triangle

Ethernet Interface

Connector	M12 D-coded 2-pin female connector
No. of Ports	2
Standards	BroadR-Reach® for 10 Mbps and 100 Mbps IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX

CAN Interface

Industrial Protocols	CAN 2.0A, CAN 2.0B, CANopen DS301, V4.02
Baudrate	10/20/50/125/250/500/800/1000 kbps, user-defined
Connector	DB9 male
Isolation	3k VDC or 2k Vrms
No. of Ports	2
Terminator	N/A, 120 ohms (by DIP)

Power Parameters

Power Consumption	86M-1620D-T: 12.6 mA @ 24 VDC 86M-1832D-T: 12.6 mA @ 24 VDC 86M-2604D-T: 127 mA @ 24 VDC 86M-2830D-T: 76.7 mA @ 24 VDC 86M-2821D-T: 85.2 mA @ 24 VDC 86M-4420-T: 143.8 mA @ 24 VDC 86M-5212U-T: 79.2 mA @ 24 VDC 86M-5250-T: 60.0 mA @ 24 VDC
-------------------	--

Physical Characteristics

Dimensions	25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in)
Weight	Under 80 g
Wiring	I/O cable, 16 to 28 AWG

Environmental Limits

Operating Temperature	-40 to 75°C (-40 to 167°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)
Altitude	2000 m ²

Standards and Certifications

EMC	EN 55032/24, EN 61000-6-2/-6-4
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF
Railway	EN 50121-4, EN 50155
Safety	UL 508
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6

MTBF

Time	86M-1620D-T: 1,115,244 hrs 86M-1832D-T: 1,149,108 hrs 86M-2604D-T: 4,173,843 hrs 86M-2821D-T: 696,245 hrs 86M-2830D-T: 1,766,037 hrs 86M-4420-T: 2,409,345 hrs 86M-5212U-T: 2,498,942 hrs 86M-5250-T: 3,306,609 hrs
Standards	Telcordia SR332

Warranty

Warranty Period	5 years
Details	See www.moxa.com/tw/warranty

Package Contents

Device	1 x ioPAC 8600 Series (86M) module
Documentation	1 x warranty card

訂購資訊

Model Name	Input/Output Interface	Input/Output Mode	Type	Channel LED
86M-1620D-T	16 x DI	24-110 VDC	Sink	P
86M-1832D-T	8 x DI	24 VDC ch-to-ch isolation	Sink/source	P
86M-2604D-T	6 x Relay	Form A (N.O.)	-	P
86M-2821D-T	8 x DO	24-110 VDC	Source	P
86M-2830D-T	8 x DO	24 VDC ch-to-ch isolation	Sink	P

2. 如果您需要產品能在高海拔地區正常運作，請與 Moxa 聯繫。

Model Name	Input/Output Interface	Input/Output Mode	Type	Channel LED
86M-4420-T	4 x AO	±10 V 0-10 V 0-20 mA 4-20 mA	-	-
86M-5212U-T	2 x 2-wire Ethernet	100BASE-TX IEEE 802.3u 10BASE-T IEEE 802.3 100 Mbps BroadR-Reach 10 Mbps BroadR-Reach	-	P
86M-5250-T	2 x CAN	CAN 2.0A CAN 2.0B CANopen DS301, V4.02	-	P

© Moxa Inc. 版權所有. 2019 年 9 月 3 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。