

EDS-4008 系列

8 埠 (可選配 4 個 802.3bt PoE 埠或 4 個 Giga uplink 連接埠) 網管型乙太網路交換器



特色與優點

- 根據 IEC 62443-4-1 開發，符合 IEC 62443-4-2 工業網路安全性標準
- Turbo Ring 和 Turbo Chain (250 台交換器，復原時間小於 20 毫秒)¹，以及透過 RSTP/STP 協議支援網路備援
- IEEE 802.3bt PoE 支援每個連接埠最高達 90 W 輸出
- 大範圍功率輸入選項適用於彈性部署
- 小巧且富有彈性的外殼設計，可輕易安裝至狹小空間。
- 支援 MXstudio，輕鬆實現可視化的工業網路管理

認證



簡介

EDS-4008 系列包含多款 8 埠網管型快速乙太網路交換器，可選配四個 1 Gbps uplink 連接埠或兩個 100M ST/SC 光纖連接埠。此系列也提供選配四個 10/100BaseT(X) 802.3af (PoE)、802.3at (PoE+) 與 802.3bt 相容乙太網路 PoE 連接埠的型號，可用於連接高頻寬 PoE 裝置。

備援乙太網路技術 (例如 Turbo Ring、Turbo Chain 與 RSTP/STP) 可增加系統的可靠性，並且改善網路骨幹的可用性。EDS-4008 系列是專門為高要求的應用所設計 (例如視訊與流程監控、ITS 和 DCS 系統) 所有應用都可從可擴充的骨幹中獲益。

EDS-4008 系列通過 IEC 62443-4-2 與 IEC 62443-4-1 工業網路安全性認證，其中包括產品安全性與安全開發生命週期需求，可協助客戶符合安全工業網路設計的合規性需求。

規格

Ethernet Interface

10/100BaseT(X) Ports (RJ45 connector)	EDS-4008-LV/-HV/-T models: 8 EDS-4008-2MST-LV/-HV/-T models: 6 EDS-4008-2MSC-LV/-HV/-T models: 6 EDS-4008-2SSC-LV/-HV/-T models: 6 EDS-4008-2GT-2GS-LV/-HV/-T models: 4 Auto negotiation speed Full/Half duplex mode Auto MDI/MDI-X connection
PoE Ports (10/100BaseT(X), RJ45 connector)	EDS-4008-4P-2GT-2GS-LVA/-LVB/-T models: 4
100BaseFX Ports (multi-mode SC connector)	EDS-4008-2MSC-LV/-HV/-T models: 2
100BaseFX Ports (multi-mode ST connector)	EDS-4008-2MST-LV/-HV/-T models: 2
100BaseFX Ports (single-mode SC connector)	EDS-4008-SSC-LV/-HV/-T models: 2
10/100/1000BaseT(X) Ports (RJ45 connector)	EDS-4008-2GT-2GS-LV/-HV/-T models: 2 EDS-4008-4P-2GS-2GT-LVA/-LVB/-T models: 2
100/1000BaseSFP Slots	EDS-4008-2GT-2GS-LV/-HV/-T models 2 EDS-4008-4P-2GT-2GS-LVA/-LVB/-T models: 2

1. 如果連接埠連結速度為 1 Gigabit 或以上，復原時間小於 < 50 毫秒

Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3ab for 1000BaseT(X) IEEE 802.3z for 1000BaseX IEEE 802.3x for flow control IEEE 802.3ad for Port Trunk with LACP IEEE 802.1Q for VLAN Tagging IEEE 802.1D-2004 for Spanning Tree Protocol IEEE 802.1w for Rapid Spanning Tree Protocol IEEE 802.1p for Class of Service IEEE 802.1X for authentication																																																				
Optical Fiber	<table border="1"> <thead> <tr> <th colspan="2" rowspan="2"></th><th colspan="3">100BaseFX</th></tr> <tr> <th colspan="2">Multi-Mode</th><th>Single-Mode</th></tr> <tr> <th colspan="2" rowspan="2">Fiber Cable Type</th><th rowspan="2">OM1</th><th>50/125 μm</th><th rowspan="2">G.652</th></tr> <tr> <th>800 MHz x km</th></tr> </thead> <tbody> <tr> <td colspan="2">Typical Distance</td><td>4 km</td><td>5 km</td><td>40 km</td></tr> <tr> <td rowspan="3">Wavelength</td><td>Typical (nm)</td><td colspan="2">1300</td><td>1310</td></tr> <tr> <td>TX Range (nm)</td><td colspan="2">1260 to 1360</td><td>1280 to 1340</td></tr> <tr> <td>RX Range (nm)</td><td colspan="2">1100 to 1600</td><td>1100 to 1600</td></tr> <tr> <td rowspan="4">Optical Power</td><td>TX Range (dBm)</td><td colspan="2">-10 to -20</td><td>0 to -5</td></tr> <tr> <td>RX Range (dBm)</td><td colspan="2">-3 to -32</td><td>-3 to -34</td></tr> <tr> <td>Link Budget (dB)</td><td colspan="2">12</td><td>29</td></tr> <tr> <td>Dispersion Penalty (dB)</td><td colspan="2">3</td><td>1</td></tr> </tbody> </table> Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power. Note: Compute the “typical distance” of a specific fiber transceiver as follows: Link budget (dB) > dispersion penalty (dB) + total link loss (dB).						100BaseFX			Multi-Mode		Single-Mode	Fiber Cable Type		OM1	50/125 μm	G.652	800 MHz x km	Typical Distance		4 km	5 km	40 km	Wavelength	Typical (nm)	1300		1310	TX Range (nm)	1260 to 1360		1280 to 1340	RX Range (nm)	1100 to 1600		1100 to 1600	Optical Power	TX Range (dBm)	-10 to -20		0 to -5	RX Range (dBm)	-3 to -32		-3 to -34	Link Budget (dB)	12		29	Dispersion Penalty (dB)	3		1
		100BaseFX																																																			
		Multi-Mode		Single-Mode																																																	
Fiber Cable Type		OM1	50/125 μm	G.652																																																	
			800 MHz x km																																																		
Typical Distance		4 km	5 km	40 km																																																	
Wavelength	Typical (nm)	1300		1310																																																	
	TX Range (nm)	1260 to 1360		1280 to 1340																																																	
	RX Range (nm)	1100 to 1600		1100 to 1600																																																	
Optical Power	TX Range (dBm)	-10 to -20		0 to -5																																																	
	RX Range (dBm)	-3 to -32		-3 to -34																																																	
	Link Budget (dB)	12		29																																																	
	Dispersion Penalty (dB)	3		1																																																	

Ethernet Software Features

Industrial Protocols	EtherNet/IP Modbus TCP PROFINET IO Device
Management	IPv4/IPv6 Flow control Back Pressure Flow Control DHCP Server/Client ARP RARP LLDP Fiber check Port Mirroring (SPAN, RSPAN) Linkup Delay SMTP SNMP Trap SNMP Inform SNMPv1/v2c/v3 RMON TFTP SFTP HTTP HTTPS Telnet Syslog Private MIB
Filter	GMRP GVRP GARP

	802.1Q VLAN IGMP Snooping v1/v2/v3 IGMP Querier
Redundancy Protocols	STP RSTP Turbo Ring v2 Turbo Chain Ring Coupling Dual-Homing Link Aggregation MSTP MRP
Security	Broadcast storm protection Rate Limit Trust access control Static Port Lock MAC Sticky HTTPS/SSL SSH RADIUS TACACS+ Access control list Login and Password Policy DHCP Snooping
Time Management	SNTP NTP Server/Client NTP Authentication IEEE 1588v2 PTP (hardware-based) Supported power profiles: IEEE 1588 Default 2008, IEC 61850-9-3-2016, IEEE C37.238-2017
Protocols	IPv4/IPv6 TCP/IP UDP ICMP ARP RARP TFTP DNS NTP Client DHCP Server DHCP Client 802.1X QoS HTTPS HTTP Telnet SMTP SNMPv1/v2c/v3 RMON Syslog
MIB	P-BRIDGE MIB Q-BRIDGE MIB IEEE8021-SPANNING-TREE-MIB IEEE8021-PAE-MIB IEEE8023-LAG-MIB LLDP-EXT-DOT1-MIB LLDP-EXT-DOT3-MIB SNMPv2-MIB RMON MIB Groups 1, 2, 3, 9
Switch Properties	
MAC Table Size	16 K
Jumbo Frame Size	9.216 KB
Max. No. of VLANs	256

VLAN ID Range	VID 1 to 4094
IGMP Groups	512
Priority Queues	4
Packet Buffer Size	1 MB

LED Interface

LED Indicators	PWR1, PWR2, STATE, FAULT, MSTR/HEAD, CPLR/TAIL, SYNC
----------------	--

Serial Interface

Console Port	RS-232 (TxD, RxD, GND), 8-pin RJ45 (115200, n, 8, 1)
--------------	--

USB Interface

USB Connector	USB Type A (Reserved)
---------------	-----------------------

Input/Output Interface

Alarm Contact Channels	1, Relay output with current carrying capacity of 1 A @ 24 VDC
Digital Input Channels	1
Digital Inputs	+13 to +30 V for state 1 -30 to +3 V for state 0 Max. input current: 8 mA
Buttons	Reset button

DIP Switch Configuration

DIP Switches	Turbo Ring, Master, Coupler, Reserve
--------------	--------------------------------------

Power Parameters

Connection	2 removable 4-contact terminal block(s)
Pre-installed Power Module	-LV/-LV-T models: PWR-100-LV -HV/-HV-T models: PWR-105-HV-I -LVA/-LVA-T models: PWR-101-LV-BP-I -LVB/-LVB-T models: PWR-103-LV-VB-I
Note	The EDS-4008 Series supports modular power supplies. The model names and power parameters are determined by the installed power module. For example: EDS-4008-T + PWR-100-LV = EDS-4008-LV-T EDS-4008-T + PWR-105-HV-I = EDS-4008-HV-T If you install a different power module, refer to the specifications of the corresponding model. For example, if you replace the power module of the EDS-4008-LV-T with the PWR-105-HV-I, refer to the specifications of the EDS-4008-HV-T.
Input Voltage	-LV/-LV-T models: 12/24/48 VDC, Redundant dual inputs -HV/-HV-T models: 110/220 VDC/VAC, Single input -LVA/-LVA-T models: 48 VDC, Redundant dual inputs -LVB/-LVB-T models: 12/24/48 VDC, Redundant dual inputs
Operating Voltage	-LV/-LV-T models: 9.6 to 60 VDC -HV/-HV-T models: 88 to 300 VDC, 85 to 264 VAC -LVA/-LVA-T models: 44 to 57 VDC (> 52 VDC for PoE+ output recommended) -LVB/-LVB-T models: 12 to 57 VDC (> 52 VDC for PoE+ output recommended)
Input Current	-LV/-LV-T models: 12-48 VDC, 1.50-0.40 A or 24 VDC, 0.70 A -HV/-HV-T models: 110-220 VAC, 50-60 Hz, 0.30-0.20 A or 110-220 VDC, 0.30-0.20 A -LVA/-LVA-T models: 48 VDC, 5.42 A -LVB/-LVB-T models: 12/48 VDC, 7.46/4.27 A or 24 VDC, 7.26 A

Power Consumption (Max.)	EDS-4008-LV(-T) models: 7.20 W EDS-4008-HV(-T) models: 8.13 W EDS-4008-2MST-LV(-T) models: 8.45 W EDS-4008-2MST-HV(-T) models: 11.13 W EDS-4008-2MSC-LV(-T) models: 8.45 W EDS-4008-2MSC-HV(-T) models: 11.09 W EDS-4008-2SSC-LV(-T) models: 8.98 W EDS-4008-2SSC-HV(-T) models: 11.37 W EDS-4008-2GT-2GS-LV(-T) models: 9.41 W EDS-4008-2GT-2GS-HV(-T) models: 11.17 W EDS-4008-4P-2GT-2GS-LVA(-T) models: Without PoE: 11.22 W With PoE: Max. 240 W for total PD power consumption @ 48 VDC input EDS-4008-4P-2GT-2GS-LVB(-T) models: Without PoE: 15.84 W With PoE: Max. 180 W for total PD power consumption @ 48 VDC input; Max. 150 W for total PD power consumption @ 24 VDC input; Max. 62 W for total PD power consumption @ 12 VDC input
Max. PoE Power Output per Port	PoE models: 90 W
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

IP Rating	IP40
Dimensions	EDS-4008(-T), EDS-4008-2MSC(-T), EDS-4008-2SSC(-T) models: 55 x 140 x 120 mm (2.2 x 5.51 x 4.72 in) EDS-4008-2MST(-T) models: 55 x 140 x 132 mm (2.2 x 5.51 x 5.2 in) EDS-4008-2GT-2GS(-T), EDS-4008-4P-2GT-2GS(-T) models: 55 x 140 x 122.5 mm (2.2 x 5.51 x 4.82 in)
Weight	EDS-4008(-T) models: 857 g (1.89 lb) EDS-4008-2MSC(-T) models: 886 g (1.95 lb) EDS-4008-2MST(-T) models: 810 g (1.79 lb) EDS-4008-2SSC(-T) models: 882 g (1.94 lb) EDS-4008-2GT-2GS(-T) models: 795 g (1.75 lb) EDS-4008-4P-2GT-2GS(-T) models: 840 g (1.85 lb)
Installation	DIN-rail mounting Wall mounting (with optional kit)
Housing	Metal

Environmental Limits

Operating Temperature	Standard Models: -10 to 60°C (14 to 140°F) Wide Temp. Models: -40 to 75°C (-40 to 167°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

Industrial Cybersecurity	IEC 62443-4-1 IEC 62443-4-2
Safety	UL 61010-2-201 EN 62368-1 (LVD)
EMC	EN 55032/35 EN 61000-6-2/-6-4

EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF
Maritime	-LV/-LV-T, PoE/PoE-T models: DNV, ABS, NK, LR
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Railway	EN 50121-4
Traffic Control	NEMA TS2
Power Substation	IEC 61850-3 IEEE 1613 Class 1
Hazardous Locations	-LV/-LV-T models: ATEX IECEX Class I Division 2

MTBF

Time	EDS-4008-LV/-LV-T models: 1,121,399 hrs EDS-4008-HV/-HV-T models: 513,575 hrs EDS-4008-2MSC-LV/-LV-T models: 1,014,299 hrs EDS-4008-2MSC-HV/-HV-T models: 492,582 hrs EDS-4008-2MST-LV/-LV-T models: 1,015,718 hrs EDS-4008-2MST-HV/-HV-T models: 492,582 hrs EDS-4008-2SSC-LV/-LV-T models: 1,015,718 hrs EDS-4008-2SSC-HV/-HV-T models: 492,582 hrs EDS-4008-2GT-2GS-LV/-LV-T models: 1,074,099 hrs EDS-4008-2GT-2GS-HV/-HV-T models: 505,936 hrs EDS-4008-4P-2GT-2GS-LVA/-LVA-T models: 923,670 hrs EDS-4008-4P-2GT-2GS-LVB/-LVB-T models: 870,865 hrs
Standards	Telcordia SR332

Warranty

Warranty Period	5 years
Details	See www.moxa.com/tw/warranty


Package Contents

Device	1 x EDS-4008 Series switch
Documentation	1 x quick installation guide 1 x product notice, Simplified Chinese 1 x product certificates of quality inspection, Simplified Chinese 1 x warranty card

尺寸


EDS-4008(-T)、EDS-4008-2MSC(-T)、EDS-4008-2SSC(-T) 型號

單位：公釐（英吋）




EDS-4008-2MST(-T) 型號

單位：公釐（英吋）



EDS-4008-2GT-2GS(-T) 、EDS-4008-4P-2GT-2GS(-T) 型號

單位：公釐（英吋）



訂購資訊

Model Name	10/ 100 BaseT(X) Ports (RJ45 Connecto r)	100 BaseFX Ports (Multi- mode SC Connecto r)	100 BaseFX Ports (Multi- mode ST Connecto r)	100 BaseFX Ports (Single- mode SC Connecto r)	PoE 10/ 100 BaseT(X) Ports (RJ45 Connecto r)	10/100/ 1000 BaseT(X) Ports (RJ45 Connecto r)	100/ 1000 BaseSFP Slots	Operating Voltage	Pre- installed Power Module	Operating Temp.
EDS-4008-LV	8	–	–	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-10 to 60° C
EDS-4008-LV-T	8	–	–	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-40 to 75° C
EDS-4008-HV	8	–	–	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-10 to 60° C
EDS-4008-HV-T	8	–	–	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-40 to 75° C
EDS-4008-2MSC- LV	6	2	–	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-10 to 60° C
EDS-4008-2MSC- LV-T	6	2	–	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-40 to 75° C
EDS-4008-2MSC- HV	6	2	–	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-10 to 60° C
EDS-4008-2MSC- HV-T	6	2	–	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-40 to 75° C
EDS-4008-2MST- LV	6	–	2	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-10 to 60° C
EDS-4008-2MST- LV-T	6	–	2	–	–	–	–	9.6 to 60 VDC	PWR-100- LV	-40 to 75° C
EDS-4008-2MST- HV	6	–	2	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-10 to 60° C
EDS-4008-2MST- HV-T	6	–	2	–	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105- HV-I	-40 to 75° C

Model Name	10/ 100 BaseT(X) Ports (RJ45 Connecto r)	100 BaseFX Ports (Multi- mode SC Connecto r)	100 BaseFX Ports (Multi- mode ST Connecto r)	100 BaseFX Ports (Single- mode SC Connecto r)	PoE 10/ 100 BaseT(X) Ports (RJ45 Connecto r)	10/100/ 1000 BaseT(X) Ports (RJ45 Connecto r)	100/ 1000 BaseSFP Slots	Operating Voltage	Pre- installed Power Module	Operating Temp.
EDS-4008-2SSC-LV	6	–	–	2	–	–	–	9.6 to 60 VDC	PWR-100-LV	-10 to 60° C
EDS-4008-2SSC-LV-T	6	–	–	2	–	–	–	9.6 to 60 VDC	PWR-100-LV	-40 to 75° C
EDS-4008-2SSC-HV	6	–	–	2	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105-HV-I	-10 to 60° C
EDS-4008-2SSC-HV-T	6	–	–	2	–	–	–	88 to 300 VDC, 85 to 264 VAC	PWR-105-HV-I	-40 to 75° C
EDS-4008-2GT-2GS-LV	4	–	–	–	–	2	2	9.6 to 60 VDC	PWR-100-LV	-10 to 60° C
EDS-4008-2GT-2GS-LV-T	4	–	–	–	–	2	2	9.6 to 60 VDC	PWR-100-LV	-40 to 75° C
EDS-4008-2GT-2GS-HV	4	–	–	–	–	2	2	88 to 300 VDC, 85 to 264 VAC	PWR-105-HV-I	-10 to 60° C
EDS-4008-2GT-2GS-HV-T	4	–	–	–	–	2	2	88 to 300 VDC, 85 to 264 VAC	PWR-105-HV-I	-40 to 75° C
EDS-4008-4P-2GT-2GS-LVA	–	–	–	–	4	2	2	44 to 57 VDC (> 52 VDC for PoE+ output recommended)	PWR-101-LV-BP-I	-10 to 60° C
EDS-4008-4P-2GT-2GS-LVA-T	–	–	–	–	4	2	2	44 to 57 VDC (> 52 VDC for PoE+ output recommended)	PWR-101-LV-BP-I	-40 to 75° C
EDS-4008-4P-2GT-2GS-LVB	–	–	–	–	4	2	2	12 to 57 VDC (> 52 VDC for PoE+ output recommended)	PWR-103-LV-VB-I	-10 to 60° C
EDS-4008-4P-2GT-2GS-LVB-T	–	–	–	–	4	2	2	12 to 57 VDC (> 52 VDC for PoE+ output recommended)	PWR-103-LV-VB-I	-40 to 75° C

配件 (選購)

Storage Kits

ABC-02-USB	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature
ABC-02-USB-T	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, -40 to 75°C operating temperature
ABC-03-microSD-T	MicroSD-based configuration backup and restoration tool, firmware upgrades, and log file storage tool for managed Ethernet switches and WLAN products, -40 to 85°C operating temperature

SFP Modules

SFP-1GEZXLC	SFP module with 1 1000BaseEZ port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZ port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHXL	SFP module with 1 1000BaseLH port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLSXL	SFP module with 1 1000BaseLS port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature
SFP-1GLXL	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GSXL	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXL-T	SFP module with 1 1000BaseLH port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXL-T	SFP module with 1 1000BaseLS port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature
SFP-1GLXL-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXL-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature
SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1FELL-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature

SFP-1FEMLC-T	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature

Power Supplies

HDR-60-24	60 W/2.5 A DIN-rail 24 VDC power supply, universal 85 to 264 VAC or 120 to 370 VDC input voltage, -30 to 70°C operating temperature
NDR-120-24	120 W/5.0 A DIN-rail 24 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature
NDR-120-48	120 W/2.5 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature
NDR-240-48	240 W/5.0 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature
MDR-40-24	DIN-rail 24 VDC power supply with 40W/1.7A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature
MDR-60-24	DIN-rail 24 VDC power supply with 60W/2.5A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature

© Moxa Inc. 版權所有.2024 年 4 月 03 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。