

# WAC-2004A Series

## Industrial wireless access controllers



### Features and Benefits

- Supports Layer 2/3 roaming
- Sub-50 ms controller-based Turbo Roaming for Wi-Fi 4 capable AWK and TAP rail devices
- Device-level redundancy via hot standby controller

### Certifications



## Introduction

The WAC-2004A Series industrial wireless access controllers feature Layer 2 and Layer 3 Controller-based Turbo Roaming technology, enabling seamless roaming across IP subnets under 50 ms to ensure uninterrupted client communication when moving between access points. The WAC-2004A Series also supports device-level redundancy with hot standby controllers to enhance network availability.

## Specifications

### Ethernet Interface

10/100/1000BaseT(X) Ports (RJ45 connector)	2 Port 1: Communications port for WAC/HA Port 2: Reserved
Standards	IEEE 802.11i for Wireless Security IEEE 802.3 for 10BaseT IEEE 802.3ab for 1000BaseT(X) IEEE 802.1X for authentication

### Ethernet Software Features

Management	IPv4 SNMPv1/v2c/v3 Syslog TCP/IP Telnet TFTP Web Console Wireless Search Utility
Security	HTTPS/SSL RADIUS SSH
Time Management	NTP Client SNTP

## Serial Interface

Console Port	RS-232 ports x 1 (DB9 male)
Flow Control	RTS/CTS, XON/XOFF
Parity	None, Even, Odd, Space, Mark

## Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
--------	--

## Wireless Access Control

Controller Failover Mode	1-on-1 hot backup
Handover Time	50 ms
Roaming Support	Turbo Roaming (L2/L3) with inter-controller capabilities
WLAN Products Supported	Layer 2 networks: Up to 190 clients roaming between 400 APs Layer 3 networks: Up to 100 clients roaming between 190 APs

## Supported Devices

TAP Products	TAP-213/323 Series
AWK Products	AWK-3131A-RTG Series

## Power Parameters

Input Current	1.2 A @ 100 VAC
Input Voltage	100 to 240 VAC
No. of Power Inputs	2
Operating Voltage	100 to 240 VAC

## Physical Characteristics

Housing	Metal
Dimensions (without ears)	304 x 440 x 44 mm (11.97 x 17.32 x 1.73 in)
Weight	4,550 g (10.03 lb)
Installation	19-inch rack mounting

## Environmental Limits

Operating Temperature	0 to 50°C (32 to 122°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

## Standards and Certifications

Safety	IEC 60950-1 UL 62368-1 IEC 62368-1
EMC	EN 55032/35 EN 61000-6-2/-6-4

EMI	CISPR 32, FCC Part 15B Class A
EMS	<p>IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV</p> <p>IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 20 V/m</p> <p>IEC 61000-4-3 RS: 1400 MHz to 2000 MHz: 10 V/m</p> <p>IEC 61000-4-3 RS: 2000 MHz to 2700 MHz: 5 V/m</p> <p>IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m</p> <p>IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV</p> <p>IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV</p> <p>IEC 61000-4-6 CS: 10 V</p> <p>IEC 61000-4-8 PFMF: 100 A/m</p>

#### Declaration

Green Product	RoHS, CRoHS, WEEE
---------------	-------------------

#### MTBF

Time	447,959 hrs
Standards	Telcordia Standard SR-332

#### Warranty


Warranty Period	5 years
Details	See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a>

#### Package Contents

Device	1 x WAC-2004A Series wireless access controller
Installation Kit	2 x cap, plastic, for RJ45 port 1 x rack-mounting kit
Cable	1 x DB9 female to RJ45
Power Supply	2 x AC power cords, C13-type, US and EU type
Documentation	1 x quick installation guide 1 x warranty card

## Dimensions

Unit: mm (inch)



## Ordering Information

Model Name	Application	Operating Temp.
WAC-2004A	Industrial wireless access controller	0 to 50°C

© Moxa Inc. All rights reserved. Updated Jan 23, 2026.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.